



Application

Moonlight is a high specification IP65 weatherproof, vandalresistantluminaire. Auniquepoly-carbonateopen lens is utilised to create a decorative appearance and obtain optimum light output anddistribution.

Ideal for:

- CarParks
- External AmenityLighting.

Body

Formed from die cast aluminium with a UVA stabilized opal polycarbonate diffuser.

Sizes

(nominal)Diamet
er: 360mm Depth:
80mm

Control Gear

Standard LED

Options Available

- Add /DALI to Cat No. for DALIDimming
- Add /EMG to Cat No. for EmergencyMode
- Add /PIR to Cat No. for InbuiltPIR

Attachments

An Inbuilt Sensor unit gives this Luminaire an intelligence of its own. When linked with the Digital Control Systems, the luminaire can offer PIR Presence Detection automatic switch on / off. Control Daylight Sensing / Dimming to create a constant working illuminance.

Lamps

All Luminaires are supplied with colour 840, 4000k LED'S as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to136lm/watt
- 50,000 HourLife
- High ColourRendering
- SelfCooling
- 5 YearGuarantee

Catalogue Codes

Wattage	Diameter	Depth	Milliamp	Catalogue Code
12.9 W	360 mm	80 mm	250 mA	SL/LED/1550/ML/OPEN/250mA
15.1 W	360 mm	80 mm	300 mA	SL/LED/1860/ML/OPEN/300mA
17.3 W	360 mm	80 mm	350 mA	SL/LED/2180/ML/OPEN/350mA

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.