



Application

Moonlight LED Square is a high specification IP65 weatherproof, vandal resistant luminaire. A unique poly-carbonate open lens is utilised to create a decorative appearance and obtain optimum light output and distribution.

Ideal for:

- Car Parks
- External Amenity Lighting

Body

Formed from die cast aluminium with a UVA stabilised opal poly-carbonate diffuser.

Sizes (nominal)

Length: 300 mm
Width: 300 mm
Diameter: N/A
Depth: 100 mm

Control Gear

- Standard LED
- DSI Dimming LED
- DALI Dimming LED

Options Available

- Emergency Mode

Attachments

- Integrated PIR Daylight Control

LED Boards

All luminaires are supplied with colour 840, 4000k LEDs as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to 63lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee

Catalogue Codes

Wattage	Length	Width	Depth	Catalogue Code
20 W	300 mm	300 mm	100 mm	SL/LED/1250/ML/SQ

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.