



Application

The NeptuneLED is designed for the hostile environment where a tough, no nonsense fitting is required. Dust tight and water-jet proof, it holds an IP65 and IK10 protection rating.

Ideal for:

- Garages
- Food Factories
- Loading Bays
- Industrial Areas

Body

Manufactured in High strength Poly-carbonate, in a light grey finish. Standard diffuser is reeded Poly-carbonate.

Sizes

(nominal) Length:
1200/1500 mm Width:
400 mm
Depth: 75 mm

Control Gear

- Standard LED
- DALI Dimming LED
- DSI Dimming LED

Options Available

Add /EMG to codes for Emergency Mode

Attachments

Add /PIR to codes for Inbuilt PIR

Lamps

All Luminaires are supplied with colour 840, 4000k LEDs as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to 136lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee



Catalogue Codes

| Wattage | Length | Width | Depth | Catalogue Code |
|---------|---------|--------|-------|-----------------------|
| 76.8 W | 1210 mm | 400 mm | 75 mm | SL/LED/12/9940/NT/HO |
| 91.0 W | 1210 mm | 400 mm | 75 mm | SL/LED/12/11940/NT/HO |
| 105.2 W | 1210 mm | 400 mm | 75 mm | SL/LED/12/13920/NT/HO |
| 93.6 W | 1510 mm | 400 mm | 75 mm | SL/LED/15/13200/NT/HO |
| 110.0 W | 1510 mm | 400 mm | 75 mm | SL/LED/15/15200/NT/HO |
| 130.0 W | 1510 mm | 400 mm | 75 mm | SL/LED/15/17400/NT/HO |

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.