



#### Application

The Neptune LED Zone is designed for the hostile environment where a tough, no nonsense fitting is required. Dust tight and explosion proof, it holds an IP66 and IK10 protection rating.

Ideal for:

- Hazardous Areas
- Highly Dusty Areas
- Under Ground Areas Containing Gas

#### Body

The body is moulded glass-fibre, reinforced polyester resin.

#### Sizes (nominal)

Length: 1250 mm  
Width: 182 mm  
Depth: 114 mm

#### Control Gear

- Standard LED
- DALI Dimming LED
- DSI Dimming LED

#### Options Available

Add /EMG to codes for Emergency  
Add /EMG/ST to codes for Self-Test Emergency  
Add /EMG/AD to codes for Addressable Emergency  
Add /DALI to codes for DALI Dimming  
Add /DSI to codes for DSI Dimming

#### LED Boards

All Luminaires are supplied with colour 840, 4000k LEDs as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

#### Main Attributes

- 125-142 lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- CRI > 80
- 5 Year Guarantee

## Catalogue Codes

Wattage	Length	Width	Depth	Catalogue Code
34.0 W	1250 mm	182 mm	114 mm	SL/LED/4770/NT/ZONE1
47.0 W	1250 mm	182 mm	114 mm	SL/LED/6290/NT/ZONE1
65.0 W	1250 mm	182 mm	114 mm	SL/LED/9260/NT/ZONE1
34.0 W	1250 mm	182 mm	114 mm	SL/LED/4770/NT/ZONE2
47.0 W	1250 mm	182 mm	114 mm	SL/LED/6290/NT/ZONE2
65.0 W	1250 mm	182 mm	114 mm	SL/LED/9260/NT/ZONE2

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.