



Application

An IP44 recessed panel luminaire utilising LED technology. This stylish fitting is designed to be used in Tee type ceilings. The front face panel provides an even distribution and can meet UGR<19 using an anti-glare diffuser.

Ideal for:

- Offices
- Commercial Areas
- Schools
- Medical Facilities
- Hospitality Areas

Body

Formed powder coated steel & aluminium housing a choice of a standard micro-prism diffuser or an anti-glare UGR<19 diffuser.

Sizes

(nominal) Length:

600/1200 mm Width:

300/600 mm

Depth: 49 mm (Recessed) 60 mm (Surface)

Control Gear

- Standard LED
- DALI Dimmable LED
- DSI Dimmable LED
- WI-FI

Options Available

- Add /EMG to codes for Emergency Mode
- Add /EMG/ST to codes for Self Test Emergency
- Add /EMG/AD to codes for Addressable Emergency
- Add /DALI to codes for DALI Dimming
- Add /DSI to codes for DSI Dimming
- Add /UGR19 to codes for UGR<19
- Add /UGR16 to codes for UGR<16
- Add /WI-FI to codes for WI-FI Control

Attachments

- Add /PIR to codes for Inbuilt PIR

LED Boards

All luminaires are supplied with colour 840, 4000k LEDs as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to 115lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- CRI>80
- 5 Year Guarantee



Catalogue Codes

Wattage	Lumens	Length	Width	Depth	Catalogue Code
19.1 W	2624 lm	597 mm	597 mm	49 mm	SL/LED/6x6/3100/PAN
20.6 W	2831 lm	597 mm	597 mm	49 mm	SL/LED/6x6/3300/PAN
22.0 W	3012 lm	597 mm	597 mm	49 mm	SL/LED/6x6/3500/PAN
23.8 W	3264 lm	597 mm	597 mm	49 mm	SL/LED/6x6/3700/PAN
24.9 W	3402 lm	597 mm	597 mm	49 mm	SL/LED/6x6/3900/PAN
29.4 W	4031 lm	597 mm	597 mm	49 mm	SL/LED/6x6/4500/PAN
26.4 W	3611 lm	597 mm	597 mm	49 mm	SL/LED/6x6/4100/PAN
27.7 W	3808 lm	597 mm	597 mm	49 mm	SL/LED/6x6/4300/PAN
30.6 W	4201 lm	597 mm	597 mm	49 mm	SL/LED/6x6/4700/PAN
38.2 W	5248 lm	597 mm	597 mm	49 mm	SL/LED/12x6/6200/PAN
41.2 W	5662 lm	597 mm	597 mm	49 mm	SL/LED/12x6/6600/PAN
44.0 W	6024 lm	597 mm	597 mm	49 mm	SL/LED/12x6/7000/PAN
47.6 W	6528 lm	597 mm	597 mm	49 mm	SL/LED/12x6/7400/PAN
49.8 W	6804 lm	597 mm	597 mm	49 mm	SL/LED/12x6/7800/PAN
52.8 W	7222 lm	597 mm	597 mm	49 mm	SL/LED/12x6/8200/PAN
55.4 W	7616 lm	597 mm	597 mm	49 mm	SL/LED/12x6/8600/PAN
58.8 W	8062 lm	597 mm	597 mm	49 mm	SL/LED/12x6/9000/PAN
61.2 W	8402 lm	597 mm	597 mm	49 mm	SL/LED/12x6/9400/PAN

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.