



### Application

Where decorative wall mounted fittings are required our PulsarLED offer exceptional performance and an IP65 rating. The Pulsar offers direct, indirect or combined direct/indirect options.

Ideal for:

- Offices
- Receptions
- Circulation Areas
- Toilets
- Apartments
- Exterior Building Walls/Fascias

### Body

Formed from 1mm Spun steel and finished in white as standard.

### Sizes

(nominal) Height:  
267/307 mm Width:  
127/212 mm Depth:  
200/285 mm

### Control Gear

- Standard LED
- DALI Dimming LED
- DSI Dimming LED

### Options Available

Add /EMG to codes for Emergency  
Add /EMG/ST to codes for Self-Test Emergency  
Add /EMG/AD to codes for Addressable Emergency  
Add /DALI to codes for DALI Dimming  
Add /DSI to codes for DSI Dimming  
Add /UP to codes for Up Light Only  
Add /DOWN to codes for Down Light Only  
Add /UP/DOWN to codes for Up & Down Light

### Attachments

Add /PIR to codes for PIR Control

### LED Boards

All luminaires are supplied with either 4300K or 5000K colour temperature. All performance DATA is taken at an ambient temperature of +25 Degrees Celsius.

### Main Attributes

- Up to 140lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- CRI > 80
- 5 Year Guarantee



### Catalogue Codes

Wattage	Lumens	Height	Width	Depth	Catalogue Code
6.2 W	726 lm	267 mm	127 mm	200 mm	SL/LED/820/PUL
7.9 W	965 lm	267 mm	127 mm	200 mm	SL/LED/1090/PUL
9.7 W	1204 lm	267 mm	127 mm	200 mm	SL/LED/1360/PUL
11.8 W	1372 lm	267 mm	127 mm	200 mm	SL/LED/1550/PUL
13.6 W	1602 lm	267 mm	127 mm	200 mm	SL/LED/1810/PUL
9.1 W	1175 lm	307 mm	212 mm	285 mm	SL/LED/1250/PUL
12.6 W	1478 lm	307 mm	212 mm	285 mm	SL/LED/1760/PUL
16.2 W	2106 lm	307 mm	212 mm	285 mm	SL/LED/2240/PUL
19.8 W	2735 lm	307 mm	212 mm	285 mm	SL/LED/2910/PUL
23.5 W	3187 lm	307 mm	212 mm	285 mm	SL/LED/3390/PUL
27.1 W	3600 lm	307 mm	212 mm	285 mm	SL/LED/3830/PUL
44.4 W	5405 lm	307 mm	212 mm	285 mm	SL/LED/5750/PUL

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.