



Application

The Radiant LED is a recessed luminaire utilising LED technology. This stylish fitting is designed to be used in Tee type ceilings while the two light strips provide an even distribution.

Ideal for:

- Offices
- Commercial Areas
- Schools
- Medical Facilities
- Hospitality Areas

Body

Formed powder coated steel & aluminium housing an anti-glare diffuser design.

Sizes

(nominal) Length:
600/1200 mm Width:
300/600 mm Depth:
28 mm

Control Gear

- Standard LED
- DALI Dimmable LED
- DSI Dimmable LED

Options Available

Add /EMG to codes for Emergency Mode
Add /EMG/ST to codes for Self Test Emergency
Add /EMG/AD to codes for Addressable Emergency

Attachments

Add /PIR to codes for Inbuilt PIR

LED Boards

All luminaires are supplied with either 4300K or 5000K colour temperature. All performance DATA is taken at an ambient temperature of +25 Degrees Celsius.

Main Attributes

- Up to 113lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee

Catalogue Codes

Wattage	Length	Width	Depth	Catalogue Code
35.0 W	595 mm	595 mm	28 mm	SL/LED/6.6/3955/RAD
35.0 W	1195 mm	295 mm	28 mm	SL/LED/12.3/3955/RAD

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.