



Application

The hollow shape of the Sapphire Ring LED is full of creativity which brings vitality into any environment. The curved light brings art inspired looks to any area.

Ideal for:

- Public Areas
- Entrance Foyer
- Corridors
- Staircases
- Hotels
- Restaurants

Body

Made from a polycarbonate outer body with a micro-prism internal diffuser. Silver as standard.

Sizes (nominal)

Available in:
- 298 mm x 51 mm

Control Gear

Standard LED

Options Available

- DALI Dimming
- Add /EMG for Emergency Mode
- Add /WS for Wire Suspension
- Add /RS for Rod Suspensions
- Add /PD for Polychromatic Diffuser
- Add /SLV for Silver
- Add /BLK for Black

Lamps

All luminaires are supplied with colour 840, 4000k LED'S as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius

Main Attributes

- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee



Catalogue Codes

Wattage	Diameter	Depth	Cat No.
18 W	298 mm	51 mm	SL/LED/1800/SPH/RING
25 W	298 mm	51 mm	SL/LED/2500/SPH/RING

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.