



Application

A unique product, large in size that creates an impressive lighting appearance. Containing multiple LED's and wattage's

Ideal for:

- Public Areas
- Entrance Foyer
- Open Office Environments.

Body

Manufactured from 1mm spun steel housing. Powder coated silver as standard.

Sizes (nominal)

- 600 mm
- 900 mm
- 1200 mm

Control Gear

Standard LED

Options Available

- High Frequency Digital Dimming
- Emergency Mode
- Wire Suspensions
- Rod Suspensions
- Polychromatic Diffuser
- Any RAL Coloured Body

Lamps

All Luminaires are supplied with colour 840, 4000k LED'S as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius

Main Attributes

- Up to 136lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee



Catalogue Codes

| Wattage | Diameter | Depth | Cat No. |
|---------|----------|--------|--------------------------|
| 38.0 W | 600 mm | 110 mm | SL/LED/6/3200/SAT/RING |
| 60.0 W | 900 mm | 110 mm | SL/LED/9/5000/SAT/RING |
| 81.0 W | 1200 mm | 110 mm | SL/LED/12/6800/SAT/RING |
| 93.8 W | 1500 mm | 110 mm | SL/LED/15/8500/SAT/RING |
| 125.0 W | 2000 mm | 110 mm | SL/LED/20/11300/SAT/RING |

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.