



Application

The Sphinx LED IP65 rated, soffit/canopy luminaire is slim with a low profile. This fitting uses high efficient LED technology to provide a higher output.

Ideal for:

- Canopy Areas
- Petroleum Stations
- Car Dealerships
- Double Height Areas

Body

The body is made from ADC12 aluminium alloy with a white stoving varnish finish. The body houses an IP65 rated poly-carbonated diffuser.

Sizes (nominal)

- 380mm x 380mm x 80mm

Control Gear

- Standard LED
- DALI Dimming LED
- DSI Dimming LED

Options Available

- Emergency Mode

Attachments

- Integrated PIR Daylight Control

LED Boards

All luminaires are supplied with colour 840, 4000k LED'S as standard. Options are available from 5000k to 6000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to 120lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee
- CRI80

Catalogue Codes

| Wattage | Length | Width | Depth | Catalogue Code |
|---------|--------|--------|-------|------------------|
| 100.5 W | 380 mm | 380 mm | 80 mm | SL/LED/10160/SPX |
| 131.7 W | 380 mm | 380 mm | 80 mm | SL/LED/13280/SPX |
| 152.0 W | 380 mm | 380 mm | 80 mm | SL/LED/15420/SPX |

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.