



Application

The StarLED is designed for the hostile environment where a tough, no nonsense IP65 fitting is required.

Ideal for:

- Security Lighting
- Building Perimeters
- Car Parks

Body

Diecast aluminium with a toughened glass cover.
IP65 Rating.

Sizes (nominal)

Length: 310/355/402/430/470 mm

Width: 220/245/295/330/360 mm

Depth: 50/55/60 mm

Control Gear

- Standard LED
- DALI Dimming LED
- DSI Dimming LED

Options Available

Add /EMG to codes for Emergency Mode

Attachments

Add /PIR to codes for Inbuilt PIR

Lamps

All luminaires are supplied with colour 840, 4000k LEDs as standard. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius

Main Attributes

- 120-130lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee

Catalogue Codes

Wattage	Length	Width	Depth	Catalogue Code
50 W	310 mm	220 mm	50 mm	SL/LED/6500/STAR
80 W	355 mm	245 mm	55 mm	SL/LED/10400/STAR
100 W	402 mm	295 mm	60 mm	SL/LED/13000/STAR
150 W	430 mm	330 mm	60 mm	SL/LED/19500/STAR
200 W	470 mm	360 mm	60 mm	SL/LED/26000/STAR

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.