



#### Application

The Star Pod LED is designed for the hostile environment where a tough, no nonsense IP65 fitting is required.

Ideal for:

- Security Lighting
- Building Perimeters
- Car Parks

#### Body

Die-cast aluminium with sectional LED boards and heat sinks. IP65 Rating.

#### Sizes (nominal)

Length: 310/355/402/430/470 mm

Width: 220/245/295/330/360 mm

Depth: 50/55/60 mm

#### Control Gear

- Standard LED
- DALI Dimming LED
- DSI Dimming LED

#### Options Available

- Add /EMG to codes for Emergency
- Add /EMG/ST to codes for Self-Test Emergency
- Add /EMG/AD to codes for Addressable Emergency
- Add /DALI to codes for DALI Dimming
- Add /DSI to codes for DSI Dimming

#### Attachments

- Add /PIR to codes for Inbuilt PIR

#### LED Boards

All luminaires are supplied with colour 840, 4000k LEDs as standard. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

#### Main Attributes

- 140lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- CRI > 80
- 5 Year Guarantee



### Catalogue Codes

Wattage	Length	Width	Depth	Catalogue Code
50 W	210 mm	220 mm	60 mm	SL/LED/7000/STAR/POD
100 W	210 mm	220 mm	60 mm	SL/LED/14000/STAR/POD
150 W	210 mm	220 mm	60 mm	SL/LED/21000/STAR/POD
200 W	280 mm	220 mm	60 mm	SL/LED/28000/STAR/POD

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.