



Application

Tarvos LED is a high specification IP65 weatherproof, vandal resistant luminaire. A unique scooped body makes the Tarvos perfect for mounting up or down for a spill of light on walls and walkways.

Ideal for:

- Building Walls
- External Architectural Lighting
- Walkway Lighting

Body

Manufactured from folded steel, vandal resistant screws and high output clear or micro-prism diffuser.

Sizes (nominal)

Height: 240 mm

Width: 220 mm

Depth: 220 mm

Control Gear

- Standard LED
- DALI Dimming LED
- DSI Dimming LED

Options Available

- Add /EMG to codes for Emergency
- Add /EMG/ST to codes for Self-Test Emergency
- Add /EMG/AD to codes for Addressable Emergency
- Add /DALI to codes for DALI Dimming
- Add /DSI to codes for DSI Dimming
- Add /MP to codes for Micro-prism Diffuser

Attachments

- Add /PIR to codes for Inbuilt PIR

LED Boards

All Luminaires are supplied with colour 840, 4000k LEDs as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- 120-140 lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- CRI > 80
- 5 Year Guarantee



Catalogue Codes

Wattage	Height	Width	Depth	Catalogue Code
5.7 W	240 mm	220 mm	220 mm	SL/LED/1050/TAR
7.5 W	240 mm	220 mm	220 mm	SL/LED/1380/TAR
9.0 W	240 mm	220 mm	220 mm	SL/LED/1590/TAR
10.5 W	240 mm	220 mm	220 mm	SL/LED/1770/TAR
11.7 W	240 mm	220 mm	220 mm	SL/LED/1980/TAR
13.2 W	240 mm	220 mm	220 mm	SL/LED/2130/TAR

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.