



#### Application

Where state of the art downlighters are required our Triton LED offers exceptional performance where a decorative appearance is required. IP54 as standard. Ideal for:

- Offices
- Receptions
- Circulation Areas
- Toilets

#### Body

Formed from Die-Cast aluminium complete with a high performance SLM heat sink to ensure life and lumen package.

#### Sizes (nominal)

- 130 x 99 mm

#### Control Gear

Standard LED

#### Options Available

- Add /WH for White Bezel
- Add /CH for Chrome Bezel
- Add /BA for Brushed Aluminium Bezel
- Add /SM for Saturn Matt Reflector
- Add /DO for Domed Opal Diffuser
- Add /FGR for Floating Glass Ring
- Add /WW for Wall Wash
- Add /FCR for Floating Coloured Ring
- Add /DCF for Dropped Colour Filters

#### Lamps

All Luminaires are supplied with colour 840, 4000k LED's as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius

#### Main Attributes

- Up to 120lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee



### Catalogue Codes

Lamp Type	Cut Out Size	Bezel Size	Depth	Cat No.
9.0 W	110 mm	130 mm	99 mm	SL/LED/800/TRI/IP54
13.0 W	110 mm	130 mm	99 mm	SL/LED/1100/TRI/IP54
23.0 W	110 mm	130 mm	99 mm	SL/LED/2000/TRI/IP54
40.0 W	110 mm	130 mm	99 mm	SL/LED/3000/TRI/IP54

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.