



Application

Where small state of the art downlighters are required our Triton IP65 LED offers exceptional performance.

Ideal for:

- Offices
- Receptions
- Circulation Area
- Toilets

Body

Formed from Die-Cast aluminium complete with a high performance SLM heat sink to ensure life and lumen package.

Sizes (nominal)

Diameter: 130 mm
Depth: 99 mm
Cutout: 110 mm

Control Gear

- Standard LED
- DALI Dimmable LED
- DSI Dimmable LED

Options Available

- Add /EMG to codes for Emergency Mode

Attachments

- Add /PIR to the Codes for PIR Control

LED Boards

All Luminaires are supplied with colour 840, 4000k LED's as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to 120lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee

Catalogue Codes

Lamp Type	Cut Out Size	Bezel Size	Depth	Cat No.
9 W	110 mm	130 mm	99 mm	SL/LED/800/TRI/IP65
13 W	110 mm	130 mm	99 mm	SL/LED/1100/TRI/IP65
23 W	110 mm	130 mm	99 mm	SL/LED/2000/TRI/IP65
40 W	110 mm	130 mm	99 mm	SL/LED/3000/TRI/IP65

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.