



Application

Where state of the art downlighters are required our TritonLED Suspended offer exceptional performance where a decorative appearance is required. IP44 as standard.

Ideal for:

- Offices
- Receptions
- Circulation Areas

Body

Formed from Die-Cast aluminium complete with a high performance SLM heat sink to ensure life and lumen package.

Sizes

(nominal) Diameter: 150mm
Depth: 170mm

Control Gear

- Standard LED
- DALI Dimmable LED
- DSI Dimmable LED

Options Available

- Add /EMG to codes for Emergency Mode

Attachments

- Add /PIR to codes for PIR Control

LED Boards

All luminaires are supplied with colour 840, 4000k LED's as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius

Main Attributes

- Up to 120lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee



Catalogue Codes

| Wattage | Diameter | Depth | Catalogue Code |
|---------|----------|--------|--------------------------|
| 6.5 W | 150 mm | 170 mm | SL/LED/700/TRI/SUR/IP44 |
| 10.8 W | 150 mm | 170 mm | SL/LED/1180/TRI/SUR/IP44 |
| 14.7 W | 150 mm | 170 mm | SL/LED/1580/TRI/SUR/IP44 |
| 21.1 W | 150 mm | 170 mm | SL/LED/2120/TRI/IP44/WS |

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.