



Application

Where state of the art downlighters are required our TritonMKII LED offer exceptional performance where a decorative appearance is required. IP54 as standard.

Ideal for:

- Offices
- Receptions
- Circulation Areas
- Toilets

Body

Formed from Die-Cast aluminium complete with a high performance SLM heat sink to ensure life and lumen package.

Sizes (nominal)

Diameter: 110 mm
Depth: 140 mm
Cutout: 90 mm

Control Gear

- Standard LED
- DALI Dimming LED
- DSI Dimming LED

Options Available

Add /EMG to codes for Emergency
Add /EMG/ST to codes for Self-Test Emergency
Add /EMG/AD to codes for Addressable Emergency
Add /DALI to codes for DALI Dimming
Add /DSI to codes for DSI Dimming

Attachments

Add /PIR to codes for Inbuilt PIR
Add /WH to codes for White Bezel
Add /CH to codes for Chrome Bezel
Add /BA to codes for Brushed Aluminium Bezel
Add /SM to codes for Saturn Matt Reflector

LED Boards

All Luminaires are supplied with colour 840, 4000k LED's as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- Up to 150lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee
- CRI > 80

Catalogue Codes

| Wattage | Lumens | Cut Out Size | Bezel Size | Depth | Catalogue Code |
|---------|---------|--------------|------------|--------|--------------------------|
| 6.2 W | 726 lm | 95 mm | 110 mm | 100 mm | SL/LED/110/820/TRI/MKII |
| 7.9 W | 965 lm | 95 mm | 110 mm | 100 mm | SL/LED/110/1090/TRI/MKII |
| 9.7 W | 1204 lm | 95 mm | 110 mm | 100 mm | SL/LED/110/1360/TRI/MKII |
| 11.8 W | 1372 lm | 95 mm | 110 mm | 100 mm | SL/LED/110/1550/TRI/MKII |
| 13.6 W | 1602 lm | 95 mm | 110 mm | 100 mm | SL/LED/110/1810/TRI/MKII |
| 6.2 W | 726 lm | 165 mm | 190 mm | 127 mm | SL/LED/190/820/TRI/MKII |
| 7.9 W | 965 lm | 165 mm | 190 mm | 127 mm | SL/LED/190/1090/TRI/MKII |
| 9.7 W | 1204 lm | 165 mm | 190 mm | 127 mm | SL/LED/190/1360/TRI/MKII |
| 11.8 W | 1372 lm | 165 mm | 190 mm | 127 mm | SL/LED/190/1550/TRI/MKII |
| 13.6 W | 1602 lm | 165 mm | 190 mm | 127 mm | SL/LED/190/1810/TRI/MKII |
| 6.2 W | 726 lm | 205 mm | 230 mm | 140 mm | SL/LED/230/820/TRI/MKII |
| 7.9 W | 965 lm | 205 mm | 230 mm | 140 mm | SL/LED/230/1090/TRI/MKII |
| 9.7 W | 1204 lm | 205 mm | 230 mm | 140 mm | SL/LED/230/1360/TRI/MKII |
| 11.8 W | 1372 lm | 205 mm | 230 mm | 140 mm | SL/LED/230/1550/TRI/MKII |
| 13.6 W | 1602 lm | 205 mm | 230 mm | 140 mm | SL/LED/230/1810/TRI/MKII |

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.