



Application

Performance inspired design combining LED technology producing direct diffused illumination, creating the ultimate working environment.

The outer diffuser can be supplied in different colours to create a different approach to lighting.

Ideal for offices or prestigious areas where luminaires have to comply with CIBSE LG7.

Body

Formed from 1mm piece bright steel, finished in white semi-Matt.

- Air handling facilities are available on request.
- Surface Mount option available on request.

Sizes (nominal)

Available in:

- 600 x 300
- 600 x 600
- 1200 x 300
- 1200 x 600
- 1500 x 300

Other Sizes can be manufactured as specials.

Control Gear

Standard

- High Frequency Driver

Options Available

- High Frequency Dimming DSI or DALI
- PIR Daylight Control Built in Sensor
- Emergency Mode
- Addressable Emergency

Attachments

An Inbuilt Sensor unit gives this Luminaire an intelligence of its own.

When linked with the Digital Control Systems, the luminaire can offer PIR Presence Detection automatic switch on / off.

Control Daylight Sensing / Dimming to create a constant working illuminance.

The luminaire can also be incorporated into a Bus-wire system eliminating the "loan worker" syndrome by illuminating designated pathways. In-fa Red remote control of one or any Bank of luminaires can be achieved by a remote hand held unit.

Main Attributes

- Up to 146lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee

Catalogue Codes

Modular Size	Lamp Rating	Length	Width	Depth	Catalogue Codes
600 x 300	2 x 8.1 w	595mm	295mm	99mm	SL/LED/6.3/2560/T-N-A/MP/LO
600 x 600	4 x 8.1 w	595mm	595mm	99mm	SL/LED/6.6/5120/T-N-A/MP/LO
1200 x 300	4 x 8.1 w	1195mm	295mm	99mm	SL/LED/12.3/5120/T-N-A/MP/LO
1200 x 600	8 x 8.1 w	1195mm	595mm	99mm	SL/LED/12.6/10240/T-N-A/MP/LO
1500 x 300	5 x 8.1 w	1495mm	295mm	99mm	SL/LED/15.3/6400/T-N-A/MP/LO
600 x 300	2 x 11.6 w	595mm	295mm	99mm	SL/LED/6.3/2940/T-N-A/MP/HO
600 x 600	4 x 11.6 w	595mm	595mm	99mm	SL/LED/6.6/5880/T-N-A/MP/HO
1200 x 300	4 x 11.6 w	1195mm	295mm	99mm	SL/LED/12.3/5880/T-N-A/MP/HO
1200 x 600	8 x 11.6 w	1195mm	595mm	99mm	SL/LED/12.6/11760/T-N-A/MP/HO
1500 x 300	5 x 11.6 w	1495mm	295mm	99mm	SL/LED/15.3/7350/T-N-A/MP/HO

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.