



#### Application

Wall Pack LED is a high specification IP65 weatherproof, vandal resistant luminaire. A unique poly-carbonate Eye-Lid lens is utilised to create a very decorative appearance and obtain optimum light output and distribution. Can be ordered with 3 LED units for wide distribution.

Ideal for:

- Car Parks
- External Amenity Lighting

#### Body

Formed from die cast aluminium with a UVA stabilized opal polycarbonate diffuser.

#### Sizes (nominal)

Length: 299 mm  
Width: 267 mm  
Diameter: N/A  
Depth: 184 mm

#### Control Gear

- Standard LED
- DSI Dimming LED
- DALI Dimming LED

#### Options Available

Add /EMG to codes for Emergency Mode  
Add /WD to codes for 3 Lamp Wide Distribution Version

#### Attachments

Add /PIR to codes for Inbuilt PIR

#### Lamps

All luminaires are supplied with colour 840, 4000k LEDs as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius

#### Main Attributes

- Up to 136lm/watt
- 50,000 Hour Life
- High Colour Rendering
- Self Cooling
- 5 Year Guarantee

## Catalogue Codes

Lamp Type	Height	Width	Depth	Catalogue Code
10.3 W	299 mm	267 mm	184 mm	SL/LED/1600/WP
14.3 W	299 mm	267 mm	184 mm	SL/LED/1950/WP
15.3 W	299 mm	267 mm	184 mm	SL/LED/2100/WP
30.9 W	299 mm	267 mm	184 mm	SL/LED/4800/WP

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.