



Application

A dual purpose recessed luminaire with side arm suspension for use in various ceilings. Can be used without the diffuser as a wall wash to increase vertical illuminance and highlight products displayed on the wall.

Body

Formed from 1.0mm bright steel and finished in a high gloss electrostatic powdercoat.

Sizes (nominal)

Available in:

- 600mm
- 1200mm

Control Gear

Standard LED

Options Available

- DALI Dimming
- Emergency Mode

Lamps

All luminaires are supplied with colour 840, 4000k LED'S as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius

Catalogue Codes

Wattage	Length	Width	Depth	Catalogue Code
21 W	600 mm	300mm	95mm	SL/LED/6/1760/CAN/UP/LO
40 W	600 mm	300mm	95mm	SL/LED/6/3300/CAN/UP/HO
43 W	1200 mm	300mm	95mm	SL/LED/12/3520/CAN/UP/LO
80 W	1200 mm	300mm	95mm	SL/LED/12/6600/CAN/UP/HO

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.