



Application

Designed HMP the Warden LED offers an IP65, anti-ligature and IK14 rating (100J).

Ideal for:

- PrisonAreas
- Industrial MaintenanceAreas
- Pit/UndergroundAreas

Body

Formed from 4mm Zintec Steel, powder coated in Silver, White or any RAL Colour required. A 5 mm poly-carbonate diffuser is combined with anti tamper screws giving the fitting its IP65/anti-ligature rating. IK14 rated. Removable Gear Tray.

Sizes (nominal)

Length: 600/1200/1500 mm

Width: 161 mm

Depth: 110 mm

Other sizes can be manufactured, as specials to order.

Control Gear

- StandardLED
- DALI DimmingLED
- DSI DimmingLED

Options Available

- Add /EMG to codes for Emergency
- Add /EMG/ST to codes for Self-Test Emergency
- Add /EMG/AD to codes for Addressable Emergency
- Add /DALI to codes for DALI Dimming
- Add /DSI to codes for DSI Dimming

Attachments

- Add /PIR to codes for Inbuilt PIR

LED Boards

All Luminaires are supplied with colour 840, 4000k LEDs as standard. Options are available from 3000k to 5000k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.

Main Attributes

- 140lm/watt
- 50,000 HourLife
- High ColourRendering
- SelfCooling
- CRI>80
- 5 YearGuarantee

Catalogue Codes

Wattage	Length	Width	Depth	Catalogue Code
19.7 W	662 mm	161 mm	110 mm	SL/LED/6/2490/WRD
23.2 W	662 mm	161 mm	110 mm	SL/LED/6/2980/WRD
26.8 W	662 mm	161 mm	110 mm	SL/LED/6/3480/WRD
27.0 W	1270 mm	161 mm	110 mm	SL/LED/12/3480/WRD
29.0 W	1270 mm	161 mm	110 mm	SL/LED/12/3929/WRD
33.1 W	1270 mm	161 mm	110 mm	SL/LED/12/4400/WRD
37.0 W	1270 mm	161 mm	110 mm	SL/LED/12/4769/WRD
44.0 W	1270 mm	161 mm	110 mm	SL/LED/12/5594/WRD
55.0 W	1270 mm	161 mm	110 mm	SL/LED/12/6704/WRD
25.0 W	1573 mm	161 mm	110 mm	SL/LED/15/3300/WRD
34.0 W	1573 mm	161 mm	110 mm	SL/LED/15/4350/WRD
37.0 W	1573 mm	161 mm	110 mm	SL/LED/15/4912/WRD
46.0 W	1573 mm	161 mm	110 mm	SL/LED/15/5962/WRD
55.0 W	1573 mm	161 mm	110 mm	SL/LED/15/6993/WRD
69.0 W	1573 mm	161 mm	110 mm	SL/LED/15/8381/WRD

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.