



#### Application

A robust designed LED batten for surface mounting.

Ideal for:

- General Lighting
- Industrial Areas
- Commercial and Domestic Areas

#### Body

Formed from 1 mm Zintec steel, pressed to a precision shape with various mounting facilities. The end caps are polycarbonate with a frosted micro-prism diffuser.

#### Sizes (nominal)

Available in:

- 1200 mm
- 1500 mm
- 1800 mm

#### Control Gear

- Standard LED
- DALI Dimmable

#### Options Available

- Emergency Mode
- End Mounted PIR
- Continuously Mounted
- Over sleeve colors to suit the environment.
- Plug & Play

#### Attachments

Various attachments are available and special attachments can be made to order.

#### Lamps

All luminaires are supplied with colour 840, 4000k LED'S as standard. Options are available from 3000k to 6500k. All LED data and performance data is taken at an ambient temperature of +25 degrees Celsius.



## Catalogue Codes

Lamp Rating	Length	Width	Depth	Catalogue Codes
30 W	1227 mm	61 mm	64 mm	SL/LED/12/3285/ZOD/MP
55 W	1227 mm	61 mm	64 mm	SL/LED/12/6470/ZOD/MP
40 W	1527 mm	61 mm	64 mm	SL/LED/15/4650/ZOD/MP
65 W	1527 mm	61 mm	64 mm	SL/LED/15/7120/ZOD/MP
50W	1791 mm	61 mm	64 mm	SL/LED/18/5725/ZOD/MP
75 W	1791 mm	61 mm	64 mm	SL/LED/18/8370/ZOD/MP

Additional lumen outputs are available and codes may vary from those stated. Please contact us for further details.

All luminaires comply with CIBSE Lighting Guide and are designed and manufactured to conform to the general requirements of BS4533. A stringent quality control operation in accordance with ISO 9001 ensures customer satisfaction. All luminaires are accredited with the CE mark.