multigraf multigraf



Technical Specifications Creasing & Folding Eurofold TOUCHLINE CF375

Feeder system suction feeder
Feeder capacity 100 mm
Paper size minimum 105 x 148 mm
Paper size maximum 375 x 660 mm
375 x 1050 mm with table extension
Paper stocks 110 to 400 gsm or max. 0.4 mm*
Control panel touchscreen
Double sheet detection ultrasonic, optional
Creasing system Multigraf Swingbar
Crease styles 2 creasing bars = 4 styles
Crease depths 3 automatic setups
Number of creases 20

Minimum crease distance 30 mm Fold system Multigraf Pro-Knife Number of folds 2 Fold length minimum 30 mm Fold length maximum 500 mm Delivery belt length 820 mm Reception tray height 120 mm Speed 5000 A4/h Dimension 1860 x 600 x 1320 mm Weight 168 kg Electrical connection 100-240 VAC, 50/60 Hz

Eurofold TOUCHLINE CF375







single fold



Eurofold TOUCHLINE CF375 supports the following common fold types:







TOUCHLINE









CJB Printing Equipment Limited Unit 17 Dukes Close Earls Way Industrial Estate Thurmaston, Leicester LE4 8EY

> 0116 2600 777 www.cjbpe.co.uk



printing equipment

^{*}Paper stocks depending on material quality.



Multigraf – Excellence in Print Finishing!

The New Dimension In Creasing & Folding -Eurofold TOUCHLINE CF375

Integrated creasing & folding all in one The TOUCHLINE generation offers more flexibility and automation than any other product in its class. The Eurofold TOUCH-LINE CF375 from Multigraf is an integrated creasing and folding system which units the two operations in one process. It handles paper stocks up to 400 gsm.

It employs the unique Multigraf Swingbar System for creasing without cracking. The sheets don't stop during the creasing process. The automated setup of the crease

depth with different positions is another fantastic feature of the TOUCHLINE CF375. The creasing bar is easily interchangeable. This new technology allows for the speeding up of the creasing process with an ac-number of creases and folds applied. curacy of 0.2 mm.

The folding section of the Eurofold TOUCH-LINE CF375 uses Multigraf's Pro-Knife System. It was designed not only to achieve a perfect folding process but also to avoid marking and scratching on the products. These electronically controlled knives are 375 x 1050 mm. also used as deflector bars, contacting the leading edge only. Due to the extra large diameter fold rollers, there is no deforma-

tion on the folded products at all. By using this technology, the TOUCHLINE CF375 runs at a consistent speed of more than 5000 A4 sheets per hour, regardless of the

TOUCHLINE is equipped with a pile feed- er using vacuum belt technology and air knife control for a perfect sheet separation. There is no additional pump needed. This offers less noise emissions in a print room environment. The maximum sheet size is

Multigraf's Eurofold TOUCHLINE CF375 can be used as an integrated creaser/folder

performing both functions in one single pass, as perforating only, the sheets are delivered to the Very simple operation a stand-alone creaser when fold- ing is not needed or as a perforator when no other operation is required.

The delivery side consists of two different output levels. For creasing and folding, the products are delivered to the upper level onto an electric shingling delivery belt with auto settings. For creasing or

lower level into a delivery tray. In this process, the sheets are not running through the fold rollers at all, avoiding de-formation. An online perforating device is available for the lower exit level. TOUCHLINE has been designed as a space saving device, standing on wheels. The floor space needed is 1860 x 600 mm only.

Multigraf's inspiration for this new product line was given by its name - TOUCHLINE. Press the button and off you go! By simply entering the necessary information through the touchscreen, the machine creates all settings automatically. A small, centralised, multifunctional operating panel offers all necessary functions for a fast production

start.



Touchscreen Very simple and menu driven operation. All elementary settings are entered directly over the touchscreen.

One touch operation

A small, centralised and

ergonomic operating panel

offers all necessary func-

tions for a fast production

Double sheet detection A professional ultrasonic double sheet detection system is available as an option which offers a 100% control of all sheets running through the machine.



Two delivery sections The delivery side consists of two different output levels. For creasing and folding, the upper delivery belt is used, for creasing only the lower reception tray.



Perforating device An online perforating device is available for the lower exit level as an option.











