

Specifications

	DC-8/32 Collator	DC-10/60 Collator
Stations	8, 16, 24, 32	10, 20, 30, 40, 50, 60
Feed System	Vacuum belt with air-blast for sheet separation	Vacuum belt with air-blast for sheet separation
Paper Transport	Twin roller belt	Twin roller belt
Bin Capacity	60 mm	60mm
Paper Size* (WxL)	Min: 120 mm x 148 mm / Max: 350 mm x 500 mm	Min: 120 mm x 148 mm / Max: 350 mm x 500 mm
Max Speed Into Stacker*	Up to 10,000 sets / hour	Up to 10,000 sets / hour
Paper Weight*	40 – 300 gsm	40 – 300 gsm
Features & Programmes	Auto calibration, left or right hand exit selection, automatic bin selection, block mode, interleaving sheet insertion, reject tray (right & left), dynamic hand-marrying unit	Auto calibration, left or right hand exit selection, automatic bin selection, block mode, interleaving sheet insertion, reject tray (right & left), dynamic hand-marrying unit
Counters	Total/batch/ejected sets	Total/batch/ejected sets
Detection	Double feed (with adjustable sensitivity) misfeed, paper jam, paper transport jam, bin empty	Double feed (with adjustable sensitivity) misfeed, paper jam, paper transport jam, bin empty
Optional On-line Accessories	DBM-120 Dynamic Bookletmaker, DBM-120T Trimmer DBM-500 Dynamic Bookletmaker, DBM-500T Trimmer DC-12JR Jogger, DBM-400STR/L Deep Pile Stacker	DBM-120 Dynamic Bookletmaker, DBM-120T Trimmer DBM-500 Dynamic Bookletmaker, DBM-500T Trimmer DC-12JR Jogger, DBM-400STR/L Deep Pile Stacker
Dimensions (WxDxH)	630 mm x 750 mm x 1702 mm	630 mm x 750 mm x 1972 mm
Net Weight	260 kg	320 kg
Power Supply / Consumption	230V 50Hz 4A	230V 50Hz 4.5A