

*Fully Automatic Double Sided Laminator
The latest addition to our popular AL-Meister series*

AL-MEISTER®
ALM3230
Auto Laminator



Fully automated operation will immeasurably save time and costs. A large volume of encapsulation or exact size lamination is possible with one touch. Excellent model for smart users. The price is less expensive and the high standard of quality is still maintained.

Automatic Trimming

AL-Meister automatically senses the size of the paper and selects accordingly.

There are two modes. Trimming with margin, which guarantees durability and lamination waterproof, and the trimming without margin, which is suitable for surface treatment.

The modes can easily be changed.

The margin amount can be adjusted.

Excellent Heating Roller System

Combined with high performance heater, it can control temperatures perfectly for smooth and flawless lamination.

High Performance Automatic Feeder

The advanced automatic feeder enables loading of up to 200 sheets. Newly innovated anti-skew mechanism enables to detect paper skewing and automatically corrects it. Thus the paper feeding has more stability for an excellent lamination. At the same time the operator's work is now markedly reduced.

AL-MEISTER ALM3230 Specifications

Model	ALM3230
Laminating Speed	1.0m/min.
Warm-Up Time	Approx. 15min. (*1)
Temperature Range	Room Temperature, 80 - 130°C
Paper Feeding	Capacity: 200 sheets, Skew Controller Knob, Paper Guide
Max. Laminating Thickness	0.4mm (400mic.)
Paper Thickness	0.07 - 0.25mm (70 - 250mic. 65 - 240g/m ²)
Max. Paper Size	330mm(W)×457mm(L)
Min. Paper Size	257mm(W)×182mm(L)
Applicable Sizes	A3 With Margin: 303x426(±0.5)mm / Without Margin: 294x417(±0.5)mm, A4 With Margin: 303x216(±0.5)mm / Without Margin: 294x207(±0.5)mm B4 With Margin: 263x370(±0.5)mm / Without Margin: 254x361(±0.5)mm, B5 With Margin: 263x188(±0.5)mm / Without Margin: 254x179(±0.5)mm
Trimming Methods	2 modes: with / without margin with A3/A4/B4/B5 self determination system, Trimmer Position Adjustment, Cutting position adjustable
Power Consumption	1200W
Power Supply	AC 220 -240V (50/60Hz)
Dimensions	1272(W)×630(D)×470(H)mm
Net Weight	44.0kg
Attachments	Instruction Manual, Power Cord, Stand with film waste box

*1 Warm-up time depends on the set temperature and/or the room temperature.

*The finish is without rounded corners.

*The finished size is accurate to within less than 0.5mm either way.

*The above specifications are the average. Please contact our local dealer for more information.

AL-ROLL FILM

- AL SAP Roll : Super Adhesive film for digital Printing, Anti-Static
- AL Silk Matt Roll : Soft and smooth touch matt finish, keeps colour better than existing matt film, scratch resistant.

Film	Type	Film Thickness	Film Width	Film Length	Q' ty/CTN
AL SAP Roll	Gloss	38μ	320mm	300m	2
		75μ	320mm	150m	2
		125μ	320mm	100m	2
	Matt	38μ	320mm	300m	2
		75μ	320mm	150m	2
		125μ	320mm	100m	2
AL SAP Single-Side Roll	Gloss	30μ	317mm	300m	2
	Matt	30μ	317mm	300m	2
AL Silk Matt Roll	Silk Matt	38μ	320mm	300m	2
		75μ	320mm	150m	2
		125μ	320mm	100m	2