

## ICBPW302718

### FEATURES

- \_\_\_\_\_ Rigorously tested for decades of use
- \_\_\_\_\_ Exceptional support from our Customer Care team
- \_\_\_\_\_ Heavy-duty stainless steel construction
- \_\_\_\_\_ Handfinished with hemmed edges and welded seams
- \_\_\_\_\_ Recessed controls for sleeker look
- \_\_\_\_\_ Infinite speed blower control
- \_\_\_\_\_ Bright halogen lighting
- \_\_\_\_\_ Transition with backdraft minimizes backward flow of cold air
- \_\_\_\_\_ Blower required (internal or remote blowers available)
- \_\_\_\_\_ Heat lamps available for 69 cm deep models only – bulbs not included
- \_\_\_\_\_ Heat sentry for safety

### ACCESSORIES

- \_\_\_\_\_ 97 cm high stainless steel backsplash with or without warming racks
- \_\_\_\_\_ 15 cm, 30 cm, 46 cm, 61 cm and 76 cm high stainless steel duct covers
- \_\_\_\_\_ Recirculating kit and filter for non-ducted applications (internal blower)

Accessories available through an authorized dealer.  
For local dealer information, visit [subzero-wolf.com/locator](http://subzero-wolf.com/locator).




### BLOWER OPTIONS

- 1014 CMH Internal Blower
- 1528 CMH Internal Blower
- 1859 CMH Internal Blower
- 1528 CMH Remote Blower
- 2028 CMH Remote Blower
- 2535 CMH Remote Blower

## PRODUCT SPECIFICATIONS

Model	ICBPW302718
Dimensions	762mmW x 457mmH x 686mmD
Weight	31 kg
Electrical Supply	220-240 VAC; 50/60 Hz
Electrical Service	≤ 6 A
Discharge Location	Vertical or Horizontal
Discharge Dimensions	250 mm Round
Bottom of Hood to Countertop	762 mm to 914 mm

## ELECTRICAL



**NOTE:** Dimensions in parenthesis are in millimeters unless otherwise specified

## DIMENSIONS

